



POOLS SPAS FURNITURE

www.sabinepools.com

**ABOVE GROUND
POOL
OWNER'S MANUAL**



**3213 COMMON STREET
LAKE CHARLES, LA
(337) 433-1193**

**1221 KALISTE SALOOM
LAFAYETTE, LA
(337) 984-9884**

**4244 WEST CONGRESS
LAFAYETTE, LA
(337) 984-9881**

**13375 HWY. 44
GONZALES, LA
(225) 647-2669**

www.SabinePools.com

Sales@SabinePools.com

MY SWIMMING POOL

Pool Manufacturer: _____

Pool Model: _____

Pool Size: _____

Pool Gallons: _____

Liner Style: _____

Filter Model: _____ Sand lbs: _____

Pump Model: _____ HP: _____

Automatic Cleaner: _____

3-Step+® Chemical Program

BioGuard – Chlorine Pool

Step 1 - Sanitize: _____
_____ tabs per wk

Step 2 - Oxidize (Shock): _____
_____ lbs per wk

Step 3 - Prevent Algae: _____
_____ oz per wk

Step 4 - Clarify: _____
_____ oz per wk

BioGuard – Saltwater Pool

Step 1 - Sanitize (Salt): _____ ideal salt level

Step 2 - Oxidize (Shock): _____
_____ lbs per wk

Step 3 - Prevent Algae: _____
_____ oz per wk

Step 4 - Clarify: _____
_____ oz per wk



Table of Contents

INTRODUCTION	2
Water Testing	3
Water Chemistry	4
Sand Filter Operation.....	5
Filter Maintenance Recommendations	6
Pool Pump & Motor	6
Electrical Requirements.....	6
Operation	6
Helpful Hints	7
Basket Cleaning	7
Ventilation	7
Leaks	7
Winterizing	7
Multiport Valve Operation	9
General Maintenance	10
Skimmer Basket	10
Pump Basket	10
Vacuuming	10
Brushing	11
Brushing the Pool	11
Brushing the Waterline	11
Skimming	11
Automatic Pool Cleaners	12
Weed Killers	12
Winterization	12
Closing your Swimming Pool	12
Warranty-Overview	14
Pump & Motor	14
Filter System	14
Sand Filter	14
Vinyl Pool Liner	14
Installation Warranty	14

INTRODUCTION

Congratulations on the purchase of your new swimming pool, and thank you for choosing Sabine Pools.

We would like to welcome you to the family of Sabine pool owners. Your pool will offer many years of family enjoyment and relaxation. Your family and swimming pool deserve only the best, and that is why we offer only the highest quality pool products and the best trained staff of pool professionals in the area. The following is a sample of the services we offer:

- * Weekly Pool Maintenance
- * Vacation Pool Service
- * Professional Service Technicians
Full-Time, Year-Round with full
fleet of fully-stocked
Service/Repair Vehicles
- * Free In-Store Computerized Pool
Water Analysis
- * Certified BioGuard Pool Chemistry
Experts
- * Convenient online shopping at
SabinePools.com
- * Service Routes / Repairs are
available in Lake Charles and
Lafayette Areas Only

Sabine Pools, Spas & Furniture
The Best in
Backyard Living!
since 1975

II. WATER TESTING

Every pool has certain chemical parameters which must be regularly measured. The most important are pH, Total Alkalinity (TA), and the level of active sanitizer. By testing these parameters at regular intervals, you'll be able to understand how swimmer load, weather, and product application affect the water. Test your pool's water approximately once per week. Plan to bring a sample (1 pint) of pool water to the Sabine Pools location nearest you once a week for a free comprehensive computerized water analysis.

The test kit that comes with your pool tests for chlorine, pH, total hardness, and TA. These are simple tests that take very little time to complete. Follow these steps for simple and accurate readings:

- Step 1:** Remove test strip from bottle. Do not touch the colored pads.
- Step 2:** Dip the strip into the pool water. Blot the strip on its side on a clean paper towel.
- Step 3:** Compare the test strip with the colors on the back of the bottle.
- Step 4:** If adjustment is necessary, bring a water sample to the Sabine location nearest you.

Ideal test readings

Chlorine = 3 - 5 ppm

pH = 7.4 - 7.6

Total Alkalinity = 125 - 150 ppm

Total Hardness = 175 - 275 ppm

Note: Test strips should be stored out of sunlight and replaced every 6 months.

III. WATER CHEMISTRY

Water chemistry can be the most intimidating thing about pool ownership. With this in mind, Sabine Pools promotes an easy, effective 3-Step+® Program. By spending just a few minutes each week on this maintenance program, your pool water will stay sparkling clean and free from algae growth. Always be sure to read and follow label directions and hazard warnings.

Ask our BioGuard water specialist at your local Sabine Pools to personalize your weekly pool care regimen at the beginning of this manual. Keeping your water clear and blue is much easier (and less expensive) than trying to correct problems due to neglect.

Bring us a water sample at least once a week during swim season and once a month during the off-season. We provide free computerized water analyses, so fill your water sample bottle (or a clean jar or Ziploc bag). Your local water specialist is your best resource for clear, sparkling blue pool water – and for enjoying your pool!

IV. FILTER OPERATION

A. POLARIS SAND FILTER SYSTEM

The purpose of the sand filter is to collect dirt and debris from the pool water. Dirt is collected in the filter as the water flows through the multiport valve at the top of the filter and is directed downward through the sand in the filter tank. Dirt and debris are collected in the sand, and clean water is returned to the swimming pool. As more dirt and debris collect in the filter, the pressure in the filter tank rises and the water-flow back to the pool becomes restricted. A pressure gauge is located on the side of the multiport valve. **Your filter should be backwashed once a week or more often if you notice a 10 psi increase on your pressure gauge before the normally scheduled backwash is due.** Backwashing is a simple task that allows the sand filter to clean itself of the collected dirt and debris.

HOW TO BACKWASH THE FILTER:

(See precautions on p. 9, Sec. VI)

- Step 1:** Turn the pump “Off”.
- Step 2:** Set multiport valve to the “Backwash” position; always rotate the valve handle in a clockwise motion.
- Step 3:** Turn pump “On”.
- Step 4:** Allow the “Backwash” cycle to operate for 2-3 minutes or until the backwash water is clean.
- Step 5:** Turn pump “Off”.
- Step 6:** Set multiport valve to the “Rinse” position; always rotate the valve handle in a clockwise motion.
- Step 7:** Turn pump “On”.
- Step 8:** Allow the “Rinse” cycle to operate for 30 seconds.
- Step 9:** Turn pump “Off”.

Note: Pump must be off before moving the multiport valve settings. Turning the settings with pump running will damage the multiport valve.

- Step 10:** Set multiport valve to the “Filter” position; rotate the valve handle in a clockwise motion always.
- Step 11:** Turn pump “On”.
- Step 12:** Open the manual air bleeder on the multiport valve, close the air bleeder once water emerges from the air bleeder.

SAND FILTER MAINTENANCE RECOMMENDATIONS

- 1) The sand in your filter is designed specifically to be used for pool filtration and this sand should be replaced every 3 years. Sabine Pools can perform this service for you. Call your local Sabine Pools for scheduling and quotes.
- 2) ROUTINE FILTER CLEANING: Your filter's sand should be chemically cleaned using Bioguard "Strip-Kwik" or "Kleen-It" twice per season. This will ensure efficient filter operation and decrease overall chemical maintenance due to increased filtering capacity.

V. POOL PUMP & MOTOR

ELECTRICAL REQUIREMENTS

- * 115 volt, 20 amp, GFCI protected dedicated circuit running electrical wiring to the equipment site.
- * Do Not use extension cords. Use of extension cords will void the electric motor warranty.

OPERATION

- * Never operate without the pump strainer pot being full of water.
- * Pool water level should be 1/2 up the skimmer face plate.

Step 1: Fill pump pot with water.

Step 2: Sand Filter System Only - Check filter multiport valve for proper port selection. (See precautions on p.9, Sec VI)

- A) Initial start-up - Use the "Backwash" multiport selection.
- B) Normal start-up - Use the "Filter" multiport selection.

Step 3: Open valve in front of pump pot to allow free flow of water from pool to pump.

Step 4: Make sure water level in pool is 1/2 up the skimmer face plate opening in the pool.

Step 5: Turn the pump on. Allow pump time to prime itself. *If using a timer: use "On"/"Off" switch on timer to activate the pump.

Step 6: For normal start-up, the pump is primed when a steady stream of water is coming out of the "Return Jet" in the pool.

Note: The Multiport valve is on the "Filter" position.

HELPFUL HINTS

Running the pump

The pool pump should run a minimum of 12 daylight hours during the summer swim season. Keep the pump lid o-ring lubricated at all times.

Note: Electric pool pump timers are available at all Sabine locations. The timer will automatically schedule your pump run times.

Basket Cleaning

Step 1: Turn pump “Off”.

Step 2: Close valve in front of pump strainer pot.

Step 3: Turn filter multiport valve to “Closed”.

Step 4: Open pump lid, remove pump basket, and empty debris.

Step 5: Replace pump basket and lid.

IMPORTANT: Basket handle must touch pump lid when basket is all the way down in the pump pot. This prevents the basket from floating when pump is “Off”, ensuring proper basket placement. Keep pump lid o-ring lubricated.

Step 6: Open valve in front of pump pot.

Step 7: Return filter multiport valve to “Filter” position.

Step 8: Turn pump “On”.

Ventilation

Keep all air vents on underside of motor free from debris to ensure proper cooling of motor.

IMPORTANT: Keep motor area free of ants and grass. Ant nests will overheat and damage the pump motor. This type of motor damage is NOT covered under the manufacturer’s warranty.

Leaks: All leaks should be fixed immediately; prolonged leaks may cause permanent damage to the electric motor.

Winterizing / Freezing Temperatures

Either run pump continuously during freezing temperatures or drain all water from the pump housing and piping when freezing temperatures are expected.

Follow these steps to drain equipment:

- Step 1:** Turn off power to the pump. Remove the drain plug from the pump to ensure the pump will drain completely.
- Step 2:** If the pump can be removed and placed in an inside dry location, this should be done.
- Step 3:** For an outdoor unprotected location, it is best to protect the equipment in a weatherproof enclosure.

Note: We recommend covering the equipment with a tarpaulin or plastic sheet to inhibit deterioration from weather. Do not wrap pump motor with plastic because condensation could form inside the motor.



VI. MULTIPORT VALVE OPERATION

The multiport valve on your sand filter directs water flow through the sand filter. The multiport valve should **never** be turned when the pump is running. The multiport valve should **always** be turned in a **clockwise** motion. There are seven positions on the multiport valve:

1. **FILTER:** This is the normal operating position. As water flows through the sand, dirt and debris are collected and clean water is returned to the pool.
2. **BACKWASH:** Water flows through the sand in a reversed direction, flushing the collected dirt and debris from the sand and discharging this water out of the waste line.
3. **RINSE:** This position is used briefly after backwashing to clear internal filter of dirty water created during the backwash cycle.
4. **WASTE:** The waste position sends waste directly to the waste line without going through the filter.
5. **CLOSED: NO FLOW - DO NOT USE THIS SETTING WITH PUMP OPERATING.**
6. **RECIRCULATE:** Water flows from pump through multiport valve returning to the pool without going through the filter.
7. **WINTERIZE:** Use only for winterizing pool. This position prevents water from remaining in the pipes and multiport valve to prevent freeze damage.



VII. GENERAL MAINTENANCE

SKIMMER BASKET

The skimmer basket needs to be checked daily and emptied accordingly.

Step 1: Remove the skimmer basket and discard any unwanted debris.

Step 2: Place skimmer basket back into the skimmer housing. The basket needs to be firmly in place before proceeding.

PUMP BASKET

The pump basket needs to be cleaned a minimum of once a week. Refer to the Pool Pump & Motor section of this manual for instructions on how to perform this task.

VACUUMING

Vacuuming is the process of removing dirt and debris from the pool floor.

The pool should be vacuumed a minimum of once a week.

*Make sure pool water level is 1/2 up skimmer face plate.

Note: Automatic vacuuming systems are available at your local Sabine Pools.

Step 1: Clean pump and skimmer basket; also, Backwash filter if circulation seems to be poor. Put Filter Valve in Filter Position to Vacuum.

Step 2: Turn pump off.

Step 3: Attach the vacuum head to the telescoping pool pole.

Step 4: Attach the vacuum head to the vacuum hose end that swivels.

Step 5: Place the vacuum head, vacuum hose, and telescoping pole into the pool. Place the unattached end of the vacuum hose over the “return jet” in the pool. Hold the hose end over the “return jet” until vacuum hose is filled with water and all air bubbles have stopped coming out of the vacuum head, which now rests on the pool floor.

Step 6: Attach the skimmer vacuum plate to the open end of the vacuum hose. Then place the skimmer vacuum plate on top of the skimmer basket located inside the wall skimmer.

Step 7: The vacuum hose and head should now have a suction going through it. Vacuum the pool floor by slowly pushing the vacuum along the floor, similar to mowing grass. The cleaned areas should be apparent. If suction decreases, recheck the items listed in Step 1.

Step 8: After vacuuming the pool, turn the pool pump off and remove the vacuum system.

Step 9: Clean pump and skimmer baskets. Backwash sand filter to ensure proper operation. Refer to Backwash Instructions, Sec IV, p. 5.

BRUSHING

Routine brushing ensures that debris and biofilm accumulation in low circulation areas are moved back into the circulation pattern of the pool for removal by the filter system. Weekly brushing of the pool walls and low circulation areas is recommended.

Brushing the pool

Attach the pool brush directly to the telescoping pole. Only a vinyl bristle brush should be used. Brush the walls and any low circulation areas with some force in a straight up and down motion.

Brushing the water line

To help prevent scum line formation at the water line of the swimming pool it is recommended that the water line be scrubbed weekly with a vinyl bristle brush or non-abrasive cleaning pad. To assist in the removal of any water line build-up, add Bioguard Off-The-Wall to your cleaning pad/brush. This chemical cleaner is completely compatible with your existing pool water chemistry.

Important: NEVER use any household cleaners when cleaning your pool. This may result in permanent damage to the vinyl liner and serious water chemistry problems.

SKIMMING

Skimming the pool surface

Attach the leaf skim net to the telescoping pole and proceed to dip out any large debris in the pool.

Skimming the pool floor

Attach the deep leaf rake to the telescoping pole. Then proceed to scoop any large debris off the bottom of the pool.

AUTOMATIC POOL CLEANERS

There are automatic pool cleaners available that will drastically reduce the amount of time spent manually cleaning the pool. Most automatic cleaners should be operated daily for optimal results. Automatic cleaners typically have a basket or debris bag that should be cleaned regularly for best results

The trained professionals at your local Sabine Pools are ready to assist you in determining the proper automatic cleaner for your swimming pool.

WEED KILLERS

Treat the outside perimeter of the pool with nutgrass killer annually. Apply the nutgrass killer according to label directions. Another option is to surround the pool with pea gravel, decorative rocks or other landscape element.

VIII. WINTERIZATION

CLOSING YOUR SWIMMING POOL

In South Louisiana, we typically have milder winters than most areas. Because of this, we generally get a longer swimming season with warmer water year around. When the swimming pool water becomes too cold to swim, you can cover your pool for the winter or leave the pool uncovered. Most pool owners who have a lot of trees cover their pools to avoid leaf problems all winter long. If you do not have a lot of trees, it is very simple to keep your pool open for the winter. Before you cover your pool, consult with the professionals at Sabine Pools to determine if covering the pool is right for you.

COVERING YOUR POOL

Step 1: CLEAN THE POOL - Before covering your pool, clean the pool thoroughly by vacuuming all debris, brushing the walls, and removing leaves from the pool. Any debris left in the pool over the winter could result in staining.

Step 2: WINTERIZE THE WATER CHEMISTRY - To protect equipment, prevent algae growth, and keep your pool water looking good over the winter, you must properly treat your water before covering your pool. You should bring a water sample into your local Sabine Pools for testing before adding winter and balancing chemicals.

There are different winterizing chemical kits available for each size pool that are specifically designed to last over the winter. You will need to run your pump for several hours after adding the winter chemicals in order to circulate them properly.

Note: Due to Louisiana's mild winters, we recommend that you have your pool water tested every month throughout the winter.

Step 3: POOL COVERS - If you are covering your pool, there are several types of pool covers available. The most popular are solid pool covers which keep rain water and sunlight out of the pool. There are several different grades of covers, so make sure you compare quality and not just price. Solid pool covers are the style designed to be used with a winterizing chemical kit described above. An above ground pool cover will come with a cable and locking winch to keep it fastened to the pool.



POOLS

SPAS

FURNITURE

ACCESSORIES

www.sabinepools.com

IX. WARRANTY - OVERVIEW

See manufacturers' warranties for conditions & limitations.

PUMP & MOTOR- Polaris Forza Pump

- * 1 year replacement warranty on parts.
- * On-site repair: labor is not warrantied; parts are warrantied only during warranty period.
- * In-store repair: bench labor is not warrantied; parts are warrantied only during warranty period.
- * Pump basket is not covered under 1 year replacement warranty.
- * Electric motor damage caused by improper electrical wiring is not covered under the terms of the limited warranty. Running the pump with an extension cord voids the warranty. (See "Pool Pump & Motor" for electrical requirements).

FILTER SYSTEM

SAND FILTER - Polaris Prestige System

- * 1 year replacement warranty on parts
- * On-site repair: labor is not warrantied; parts are warrantied only during warranty period.
- * In-store repair: Bench labor is warrantied for a period of 1 year.

VINYL POOL LINER

- * 15 year pro-rated warranty against seam failure only.
- * Liner seam failure warranty is a manufacturer's part replacement warranty only, and does not include reinstallation labor, chemicals, loss of water, etc.
- * Liner seam failure warranty determination is done by the manufacturer only.

Non-Warrantied Pool Liner Items Include:

- * Liner punctures/holes, other than seam failure.
- * Liner bead coming out of liner track.
- * Wrinkles in liner.
- * Liner pattern discoloration of any type.

INSTALLATION WARRANTY

- Sabine Pools does not install above ground pools. Therefore, there is no warranty on installation.

Thank you for choosing Sabine Pools. It is our goal to exceed your expectations. We welcome any feedback that you can provide us, on this manual and on our everyday business services. Please offer suggestions to your local manager, or email us at Sales@SabinePools.com. We appreciate your positive reviews on our website at <https://sabinepools.com/reviews/>.



POOLS SPAS FURNITURE

www.sabinepools.com

The Best in
Backyard
Living!

since 1975